



# ECO-788

## Clay Strippable Adhesive

Strippable, Clay Wallcovering Adhesive

Product Number(s): 18605, 18601

Base: Clay

### Product Information

**General Properties:** The second part of a two-part wallcovering primer and adhesive system. Must be used in conjunction with ECO-988 Pigmented Wallpaper Primer for desired results.

- **Machinable**
- **Maximum wet tack**
- **Strippable with most fabric-backed vinyl wallcoverings**
- **LEED compliant**
- **NSF/ANSI 342 compliant**

**Recommended Uses:** For use with all types and weights of wallcovering

**Compatible Coatings:** For desired results, ECO-988 Pigmented Wallpaper Primer must be used with ECO-788 Clay Adhesive

**Mildew-Resistant:** All Roman products contain biocides for in-can preservation

### Specification Data

**Coverage:** Up to approx. 200 sq. ft. per gallon

**VOC (actual/regulatory):** 0% / 0 g/L as calculated per EPA Method 24

**Storage:** Avoid freezing; keep in cool, dry place.

**Drying Time:** Drying time will vary depending on the temperature, ventilation and humidity of the room.



Technical Data: ECO-788

Updated: 06/29/22

## Application Instructions

**Surface Preparation:** Surface must be free from mold, mildew, grease and other residues; dry, smooth and structurally sound. Refer to the [www.epa.gov](http://www.epa.gov) website for guidelines on cleaning/removing mold & mildew. Allow walls to dry, preferably below 2% moisture. Priming required with ECO-988 Pigmented Wallpaper Primer. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

**Dilution:** Do not dilute.

**Application Method:** Use only when the room temperature is above 50°F. Apply an even coat of adhesive at recommended spread rate using a pasting machine or roller. Do not overspread. Avoid contact with the surface of embossed, textured or delicate wallcoverings. Book according to the wallcovering manufacturer's instructions.

**Clean-Up:** Before the adhesive dries, remove any excess with clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls.

## Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Roman Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

## Limited Warranty

Roman Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

## Caution

**Store in a cool, dry place. DO NOT FREEZE!** Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.

**Roman Products, LLC – Calumet City, Illinois**  
**For Technical Help:** Call 708-891-0770 or **Email:** [technicalhelp@romandec.com](mailto:technicalhelp@romandec.com)  
[www.romanproducts.com](http://www.romanproducts.com)