



GH-57

Universal Wallpaper Paste

Strippable, Non-Staining Wallcovering Adhesive

Product Number(s): 207803, 207805, 207811

Base: Synthetic polymer

Product Information

General Properties: GH-57 Universal Wallpaper Paste makes hanging borders and wallcovering easy. This adhesive may be used on most sealed surfaces except poor quality latex paint.

- **Extended open time & slip**
- **Excellent adhesion**
- **May be used with pre-pasted or unpasted wallcovering**

Recommended Uses: Hanging borders, light and medium-weight wallcovering on sealed, painted surfaces

NOT Recommended for: Bare drywall, extremely rough surfaces such as concrete block, stucco and other rough, highly textured surfaces, and poor quality latex paint.

Compatible Coatings: All ROMAN[®] primers

Mildew-Resistant: All Roman products contain biocides for in-can preservation

Specification Data

Percent Solids: Approximately 10.3%

Coverage: Up to approx. 250 square feet per gallon

Viscosity: Approximately 14,000 cps

VOC (actual): 2.55% (≤50 g/L)

VOC (regulatory): ≤ 250 g/L

Storage: Avoid freezing; keep in cool, dry place

Drying Time: Drying time will vary depending on the temperature, ventilation and humidity of the room.

Application Instructions

Surface Preparation: Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for loose wallcoverings. Repair all unsound surfaces. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier. To check for poor quality latex paint, cut an "x" in the wall and apply clear tape over it. Remove quickly; if there is paint on the tape, it is of poor quality.

Dilution: Do not dilute.

Application Method: Use only when the room temperature is above 50°F. Apply an even coat, covering the entire surface of the wallcovering.

Clean-Up: Before the adhesive dries, remove any excess with warm, clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls. Adhesive may be difficult to remove after it has dried.

Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Decorating Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

Limited Warranty

Roman Decorating Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

Caution

Store in a cool, dry place. DO NOT FREEZE! Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.