



SAFETY DATA SHEET

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name PRO-732 Extra Strength™ Clay Wallcovering Adhesive

Recommended use of the chemical and restrictions on use

Application Adhesive - Construction, Wallcovering.

Uses advised against Use only for intended applications.

Details of the supplier of the safety data sheet

Supplier Roman Products, LLC
824 State Street
Calumet City, IL
60409
United States
Tel: 708-891-0770
Fax: 708-891-4746
technicalhelp@romandec.com

Emergency telephone number

Emergency telephone Tel: 708-891-0770

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status This Product is Not Hazardous under the OSHA Hazard Communication Standard.

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Label elements

Hazard statements NC Not Classified

Other hazards

None known.

3. Composition/information on ingredients

Mixtures

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

Kaolin CAS number: 1332-58-7 Substance with National workplace exposure limits.	25 - <50%
Classification Not Classified	
Proprietary CAS number: Proprietary	5 - <10%
Classification Combustible Dust - USH01	
Proprietary salt CAS number: Proprietary	3 - <5%
Classification Ox. Sol. 2 - H272 Eye Irrit. 2 - H319	
Quartz (SiO₂) CAS number: 14808-60-7 Substance with National workplace exposure limits.	0.5 - <1%
Classification STOT RE 2 - H373	
Titanium dioxide CAS number: 13463-67-7 Substance with National workplace exposure limits.	0.5 - <1%
Classification Not Classified	

The full text for all hazard statements is displayed in Section 16.

Ingredient notes The exact identity is withheld as a trade secret in accordance with 29 CFR 1910.1200. The exact percentage/concentration is withheld as a trade secret in accordance with 29 CFR 1910.1200.

4. First-aid measures

Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin Contact	It is important to remove the substance from the skin immediately. Remove contamination with soap and water or recognized skin cleansing agent. In the event of any sensitization symptoms developing, ensure further exposure is avoided. Get medical attention if symptoms are severe or persist after washing. If adhesive bonding occurs, do not force skin apart.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues. If adhesive bonding occurs, do not force eyelids apart.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known. May cause discomfort if swallowed.
Skin contact	May bond skin and eyes. Prolonged and frequent contact may cause redness and irritation. The product contains a small amount of sensitizing substance. May cause skin sensitization or allergic reactions in sensitive individuals.
Eye contact	May bond skin and eyes. Prolonged or repeated exposure may cause the following adverse effects: Pain or irritation.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. May cause sensitization or allergic reactions in sensitive individuals.
-----------------------------	--

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Oxides of carbon. Oxides of nitrogen.

Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapors. Do not touch or walk into spilled material.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Do not handle until all safety precautions have been read and understood. Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin, eyes and clothing. Use only in well-ventilated areas. Use only when the room temperature is above: 50 °F. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Store in tightly-closed, original container in a dry and cool place. Do not freeze. Keep containers upright. Protect containers from damage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

Kaolin

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ respirable fraction
A4

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

Proprietary

Long-term exposure limit (8-hour TWA): OSHA, PEL 15 mg/m³ total dust
 Long-term exposure limit (8-hour TWA): OSHA, PEL 5 mg/m³ respirable fraction
 Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³ inhalable fraction
 Long-term exposure limit (8-hour TWA): ACGIH 3 mg/m³ respirable dust
 (Particulates Not Otherwise Regulated)

Quartz (SiO₂)

Long-term exposure limit (8-hour TWA): OSHA 0.05 mg/m³ respirable dust
 Long-term exposure limit (8-hour TWA): ACGIH 0.025 mg/m³ respirable fraction
 A2

Titanium dioxide

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³
 A4
 Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust
 ACGIH = American Conference of Governmental Industrial Hygienists.
 OSHA = Occupational Safety and Health Administration.
 A4 = Not Classifiable as a Human Carcinogen.
 A2 = Suspected Human Carcinogen.

Ingredient comments

The constituents listed are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits. The product contains no other substances classified as hazardous to health by an OEL value in concentrations which should be taken into account.

Quartz (SiO₂) (CAS: 14808-60-7)

Immediate danger to life and health 25 mg/m³ 50 mg/m³

Titanium dioxide (CAS: 13463-67-7)

Immediate danger to life and health 5000 mg/m³

Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with OSHA 1910.133.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body protection

Wear appropriate clothing to prevent skin contamination.

Hygiene measures

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

Respiratory protection	No specific recommendations. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved.
Environmental exposure controls	Keep container tightly sealed when not in use. Avoid release to the environment.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Paste.
Color	Beige.
Odor	Mild.
Odor threshold	No data available.
pH	9.0
Melting point	0°C/32°F
Initial boiling point and range	100°C/212°F
Flash point	No data available.
Evaporation rate	No data available.
Flammability (solid, gas)	No data available.
Upper/lower flammability or explosive limits	No data available.
Vapor pressure	No data available.
Vapor density	No data available.
Relative density	1.34
Solubility(ies)	Miscible with water.
Partition coefficient	No data available.
Auto-ignition temperature	No data available.
Decomposition Temperature	No data available.
Viscosity	105000 cP
Explosive properties	No data available.
Oxidizing properties	No data available.
Volatile organic compound	0.18%

10. Stability and reactivity

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

Conditions to avoid	Avoid freezing. Avoid exposure to high temperatures or direct sunlight.
Materials to avoid	Do not mix with other chemicals. Avoid contact with acids and alkalis.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Oxides of carbon. Oxides of nitrogen.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Summary The product contains a small amount of sensitizing substance. May cause skin sensitization or allergic reactions in sensitive individuals.

Skin sensitization

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance/a group of substances which may cause cancer. IARC Group 1
Carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known. May cause discomfort if swallowed.
Skin Contact	May bond skin and eyes. Prolonged and frequent contact may cause redness and irritation. The product contains a small amount of sensitizing substance. May cause skin sensitization or allergic reactions in sensitive individuals.
Eye contact	May bond skin and eyes. Prolonged or repeated exposure may cause the following adverse effects: Pain or irritation.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.
Medical considerations	Skin disorders and allergies.

Toxicological information on ingredients.

Kaolin

Toxicological effects Not regarded as a health hazard under current legislation.

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >5000 mg/kg, Dermal, Rat

Proprietary salt

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 3430 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >5000 mg/kg, Dermal, Rat

Skin corrosion/irritation

Animal data Dose: 0.5g, 4 hours, Rabbit Erythema/eschar score: No erythema (0). Edema score: No oedema (0). Primary dermal irritation index: 0

Serious eye damage/irritation

Serious eye damage/irritation Dose: 95.7 mg, 72 hours, Rabbit

Skin sensitization

Skin sensitization Local Lymph Node Assay (LLNA) - Mouse: Not sensitizing.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative.

Genotoxicity - in vivo DNA damage and/or repair: Negative.

Carcinogenicity

IARC carcinogenicity IARC Group 2A Probably carcinogenic to humans.

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEL >1500 mg/kg/day, Oral, Rat P

Reproductive toxicity - development Developmental toxicity: - NOAEL: >1500 mg/kg/day, Oral, Rat

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL ≥1500 mg/kg/day, Oral, Rat Read-across data.

Aspiration hazard

Aspiration hazard Not relevant.

12. Ecological information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No data available.

Mobility in soil

Mobility The product is water-soluble and may spread in water systems.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Do not empty into drains. Dispose of contents/container in accordance with national regulations.

14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

UN Number

UN No. (International) Not applicable.

UN No. (DOT) Not applicable.

UN proper shipping name

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

Proper shipping name (International) Not applicable.

Proper shipping name (DOT) Not applicable.

Transport hazard class(es)

Transport Labels (International) No transport warning sign required.

DOT transport labels
No transport warning sign required.

Packing group

Packing group (International) Not applicable.

DOT packing group Not applicable.

Environmental hazards

Environmentally Hazardous Substance
No.

Special precautions for user

Not applicable.

DOT reportable quantity Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

The following ingredients are listed:

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed:

Sodium hydroxide

Final CERCLA RQ: 1000(454) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

The following ingredients are listed:

SARA 313 Emission Reporting

The following ingredients are listed:

3-Iodo-2-propynyl butylcarbamate

1.0 %

Proprietary salt

1.0 %

Amorphous silica

1.0 %

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

CAA Accidental Release Prevention

None of the ingredients are listed.

OSHA Highly Hazardous Chemicals

The following ingredients are listed:

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed:

Quartz (SiO₂)

Carcinogen.

Titanium dioxide

Carcinogen.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed:

Quartz (SiO₂)

Sodium hydroxide

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed.

California Directors List of Hazardous Substances

The following ingredients are listed:

Quartz (SiO₂)

Amorphous silica

Sodium hydroxide

Massachusetts "Right To Know" List

The following ingredients are listed:

Kaolin

Proprietary salt

2-Amino-2-methylpropanol

Quartz (SiO₂)

Titanium dioxide

Glycerol

Amorphous silica

Sodium hydroxide

Rhode Island "Right To Know" List

The following ingredients are listed:

Kaolin

Proprietary salt

Quartz (SiO₂)

Titanium dioxide

Glycerol

Sodium hydroxide

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

Minnesota "Right To Know" List

The following ingredients are listed:

Kaolin

Quartz (SiO₂)

Titanium dioxide

Glycerol

Amorphous silica

Sodium hydroxide

New Jersey "Right To Know" List

The following ingredients are listed:

Kaolin

3-Iodo-2-propynyl butylcarbamate

2-Amino-2-methylpropanol

Quartz (SiO₂)

Titanium dioxide

Glycerol

Sodium hydroxide

Pennsylvania "Right To Know" List

The following ingredients are listed:

Kaolin

Proprietary salt

2-Amino-2-methylpropanol

Quartz (SiO₂)

Titanium dioxide

Glycerol

Amorphous silica

Sodium hydroxide

Inventories

US - TSCA

Some of the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed.

16. Other information

PRO-732 Extra Strength™ Clay Wallcovering Adhesive

Abbreviations and acronyms used in the safety data sheet	ATE: Acute Toxicity Estimate. IATA: International Air Transport Association. ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. LC ₅₀ : Lethal Concentration to 50 % of a test population. LD ₅₀ : Lethal Dose to 50% of a test population (Median Lethal Dose). PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative. MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. BCF: Bioconcentration Factor. EC ₅₀ : 50% of maximal Effective Concentration. NOEC: No Observed Effect Concentration. NOAEL: No Observed Adverse Effect Level.
Training advice	Read and follow manufacturer's recommendations.
Revision comments	This is the first issue.
Revision date	8/9/2018
SDS No.	7577
Hazard statements in full	H272 May intensify fire; oxidizer. H319 Causes serious eye irritation. H373 May cause damage to organs through prolonged or repeated exposure. USH01 May form combustible dust concentrations in air.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.