



PRO-774

Clay Strippable Adhesive

Clay, Strippable Wallcovering Adhesive

Product Number(s): 10605

Base: Clay and Modified starches

Product Information

General Properties: Commercial grade clay adhesive designed to hold the heaviest wallcoverings. PRO-774 is the preferred adhesive for large commercial jobs such as hotels, office buildings and hospitals.

- **Contractor strength**
- **Machinable**
- **Maximum wet-tack**
- **Strippable with most fabric-back wallcoverings**

Recommended Uses: Medium to heavy weights of wallcoverings including commercial weight (Type II and Type III) wallcoverings

Compatible Coatings: All ROMAN[®] primers

Substrates: Apply over new bare drywall with fabric-backed wallcovering or over a ROMAN[®] primer, such as PRO-977 Ultra Prime[®]

Mildew-Resistant: All Roman products contain biocides for in-can preservation

Specification Data

Percent Solids: Approximately 32%

Coverage: Up to approx. 200 square feet per gallon

Viscosity: Approximately 40,000 cps

VOC (actual): ≤1%

VOC (regulatory): ≤5 g/L

Storage: Avoid freezing; keep in cool, dry place.

Drying Time: Drying time will vary depending on the temperature, ventilation, and humidity of the room.



Technical Data: PRO-774

Updated: 06/29/22

Application Instructions

Surface Preparation: Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, loose wallcoverings, damaged wallboard or plaster. Repair all unsound surfaces. Priming of bare drywall is not required with fabric-backed wallcoverings. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

Dilution: Dilute with up to one pint of clean water per gallon. DO NOT OVER DILUTE.

Application Method: Use only when the room temperature is above 50°F. Apply an even coat of adhesive with a pasting machine, brush or roller. Avoid contact with the surface of embossed, textured or delicate wallcoverings. For pasting machine use, thin with a maximum of one pint of water per gallon of adhesive.

Clean-Up: Before the adhesive dries, remove the excess with clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls.

Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

Limited Warranty

Roman Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

Caution

Store in a cool, dry place. DO NOT FREEZE! Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.

Roman Products, LLC – Calumet City, Illinois

For Technical Help: Call 708-891-0770 or Email: technicalhelp@romandec.com

www.romanproducts.com