



PRO-909

Vinyl Prep® Primer

Clear Wallcovering Primer

Product Number(s): 10205, 10201

Base: 100% acrylic polymer

Product Information

General Properties: Economical water-based primer for preparing sound acrylic or latex paint on sealed drywall for wallcovering installation.

- Better than sizing
- Dries clear
- Low odor, no spatter

Recommended Uses: To prepare walls for wallcovering installation, apply over sound drywall primed or painted with an acrylic or latex primer or paint

NOT Recommended For: Bare or unsealed drywall, vinyl-over-vinyl applications or conditions that require a white hiding primer, such as patched walls or dark colors. In these cases, ROMAN's PRO-977 Ultra Prime® is recommended. Not recommended for direct application over oil-based primers or paints.

Compatible Coatings: Most water-based products and all ROMAN® adhesives

Substrates: Sound acrylic or latex paint on sealed drywall; promotes even drying of the adhesive

Mildew-Resistant: All Roman products contain biocides for in-can preservation

Specification Data

Coverage: Up to approx. 400-450 square feet per gallon

VOC (regulatory): ≤50 g/L

Drying Time: Typically dry-to-touch in approximately one hour and ready for wallcovering installation in three hours. Low temperature, high humidity and poor ventilation will slow down the drying process.



Technical Data: PRO-909, VINYL PREP®

Updated: 06/29/22

Application Instructions

Surface Preparation: Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, damaged wallboard or plaster. Repair all unsound surfaces. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

After completion of the required surface preparation, it is critical to test the surface with the recommended primer or adhesive to ensure compatibility. Select a small, inconspicuous area of the surface for testing and apply the primer as specified. Inspect test area after 24 hours for any defects or inconsistencies before proceeding with installation of wallcovering.

Dilution: Do not dilute.

Application Method: Use only when the room temperature is above 50°F. Apply at recommended spread rate using roller, or spraying system. Do not overspread.

Airless Spray:	PSI Capable:	minimum 3000 PSI
	Hose:	3/8" I.D.
	Tip Size:	.015 and larger
	Gun PSI:	1500-1700

Clean-Up: Before the primer dries, remove any excess with clean water. Brushes and rollers should be cleaned immediately after use with a mild soap and clean, warm water.

Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

Limited Warranty

Roman Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

Caution

Store in a cool, dry place. DO NOT FREEZE! Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.

Roman Products, LLC – Calumet City, Illinois
For Technical Help: Call 708-891-0770 or Email: technicalhelp@romandec.com
www.romanproducts.com