



SAFETY DATA SHEET

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Recommended use of the chemical and restrictions on use

Application Primer.

Uses advised against Use only for intended applications.

Details of the supplier of the safety data sheet

Supplier Roman Products, LLC
824 State Street
Calumet City, IL
60409
United States
Tel: 708-891-0770
Fax: 708-891-4746
technicalhelp@romandec.com

Emergency telephone number

Emergency telephone Tel: 708-891-0770

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status This Product is Not Hazardous under the OSHA Hazard Communication Standard.

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Aquatic Acute 3 - H402

Label elements

Hazard statements H402 Harmful to aquatic life.

Precautionary statements P273 Avoid release to the environment.
P501 Dispose of contents/ container in accordance with national regulations.

Other hazards

None known.

3. Composition/information on ingredients

Mixtures

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Titanium dioxide CAS number: 13463-67-7 Substance with National workplace exposure limits.	5 - <10%
Classification Not Classified	
Ammonia CAS number: 1336-21-6 M factor (Acute) = 1	0.25 - <0.5%
Classification Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335 Aquatic Acute 1 - H400	
Phosphoric acid CAS number: 7664-38-2	0.025 - <0.25%
Classification Skin Corr. 1B - H314 Eye Dam. 1 - H318	

The full text for all hazard statements is displayed in Section 16.

Ingredient notes The exact percentage/concentration is withheld as a trade secret in accordance with 29 CFR 1910.1200.

4. First-aid measures

Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin Contact	It is important to remove the substance from the skin immediately. Remove contamination with soap and water or recognized skin cleansing agent. In the event of any sensitization symptoms developing, ensure further exposure is avoided. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known. May cause discomfort if swallowed.
Skin contact	May be slightly irritating to skin. The product contains a small amount of sensitizing substance. May cause skin sensitization or allergic reactions in sensitive individuals.
Eye contact	May be slightly irritating to eyes.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. May cause sensitization or allergic reactions in sensitive individuals.
-----------------------------	--

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Oxides of carbon. Oxides of nitrogen.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapors. Do not touch or walk into spilled material.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Do not handle until all safety precautions have been read and understood. Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin, eyes and clothing. Use only in well-ventilated areas. Use only when the room temperature is above: 50 °F. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Store in tightly-closed, original container in a dry and cool place. Do not freeze. Keep containers upright. Protect containers from damage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

Titanium dioxide

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

A4

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Phosphoric acid

Long-term exposure limit (8-hour TWA): OSHA 1 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 1 mg/m³

Short-term exposure limit (15-minute): ACGIH 3 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

A4 = Not Classifiable as a Human Carcinogen.

Ingredient comments The constituents listed are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.
The product contains no other substances classified as hazardous to health by an OEL value in concentrations which should be taken into account.

Titanium dioxide (CAS: 13463-67-7)

Immediate danger to life and health 5000 mg/m³

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Phosphoric acid (CAS: 7664-38-2)

Immediate danger to life and health 1000 mg/m³

Exposure controls

Appropriate engineering controls	Provide adequate ventilation.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with OSHA 1910.133.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.
Other skin and body protection	Wear appropriate clothing to prevent skin contamination.
Hygiene measures	Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.
Respiratory protection	No specific recommendations. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved.
Environmental exposure controls	Keep container tightly sealed when not in use. Avoid release to the environment.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Viscous liquid.
Color	White.
Odor	Mild.
Odor threshold	No data available.
pH	9.3
Melting point	0°C/32°F
Initial boiling point and range	100°C/212°F
Flash point	No data available.
Evaporation rate	No data available.
Flammability (solid, gas)	No data available.
Upper/lower flammability or explosive limits	No data available.
Vapor pressure	No data available.

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Vapor density	No data available.
Relative density	1.33
Solubility(ies)	Miscible with water.
Partition coefficient	No data available.
Auto-ignition temperature	No data available.
Decomposition Temperature	No data available.
Viscosity	5000 cP
Explosive properties	No data available.
Oxidizing properties	No data available.
Volatile organic compound	0% (EPA Method 24)

10. Stability and reactivity

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	Avoid freezing. Avoid exposure to high temperatures or direct sunlight.
Materials to avoid	Do not mix with other chemicals. Avoid contact with acids and alkalis.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Oxides of carbon. Oxides of nitrogen.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Summary	The product contains a small amount of sensitizing substance. May cause skin sensitization or allergic reactions in sensitive individuals.
Skin sensitization	Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	Contains a substance/a group of substances which may cause cancer. IARC Group 1 Carcinogenic to humans.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known. May cause discomfort if swallowed.
Skin Contact	May be slightly irritating to skin. The product contains a small amount of sensitizing substance. May cause skin sensitization or allergic reactions in sensitive individuals.
Eye contact	May be slightly irritating to eyes.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.
Medical considerations	Skin disorders and allergies.

Toxicological information on ingredients.

Titanium dioxide

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Mouse

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ 5.09 mg/l, Inhalation, Rat

Skin corrosion/irritation

Animal data Dose: 0.5 g, 4 hours, Rabbit Erythema/eschar score: Very slight erythema - barely perceptible (1). Not irritating.

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Serious eye damage/irritation

Serious eye damage/irritation Dose: 57 mg, 1 second, Rabbit Not irritating.

Skin sensitization

Skin sensitization Local Lymph Node Assay (LLNA) - Mouse: Not sensitizing.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative.

Genotoxicity - in vivo Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity NOEC 50 mg/m³, Inhalation, Rat

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - development Developmental toxicity:, Maternal toxicity: - NOAEL: 1000 mg/kg/day, Oral, Rat

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOEL 24000 mg/kg/day, Oral, Rat

Aspiration hazard

Aspiration hazard Not relevant.

Ammonia

Skin corrosion/irritation

Animal data Dose: 0.5 mL 12%, 4 hours, Rabbit Corrosive.

Serious eye damage/irritation

Serious eye damage/irritation Corrosivity to eyes is assumed.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative.

Genotoxicity - in vivo Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity NOAEL 256 mg/kg/day, Oral, Rat Read-across data.

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEL 1500 mg/kg/day, Oral, Rat P Read-across data.

Reproductive toxicity - development Developmental toxicity: - NOAEL: 100 mg/kg/day, Oral, Rabbit

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H335 May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 250 mg/kg/day, Oral, Rat

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

12. Ecological information

Toxicity Harmful to aquatic life.

Ecological information on ingredients.

Ammonia

Toxicity	Aquatic Acute 1 - H400 Very toxic to aquatic life.
<u>Acute aquatic toxicity</u>	
LE(C)₅₀	0.1 < L(E)C ₅₀ ≤ 1
M factor (Acute)	1
Acute toxicity - fish	LC ₅₀ , 96 hours: 11 mg/l, Oncorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	LC ₅₀ , 48 hours: 25.4 mg/l, Daphnia magna
<u>Chronic aquatic toxicity</u>	
Chronic toxicity - fish early life stage	NOEC, 61 days: 1.2 mg/l, Oncorhynchus gorbuscha

3-Iodo-2-propynyl butylcarbamate

Toxicity	Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410 Very toxic to aquatic life with long lasting effects.
<u>Acute aquatic toxicity</u>	
LE(C)₅₀	0.01 < L(E)C ₅₀ ≤ 0.1
M factor (Acute)	10
Acute toxicity - aquatic invertebrates	LC ₅₀ , 48 hours: 0.645 ppm, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 0.022 mg/l, Desmodium subspicatus
<u>Chronic aquatic toxicity</u>	
NOEC	0.001 < NOEC ≤ 0.01
Degradability	Rapidly degradable
M factor (Chronic)	1
Chronic toxicity - fish early life stage	NOEC, 35 days: 0.0084 mg/l, Pimephales promelas (Fat-head Minnow)
Chronic toxicity - aquatic invertebrates	NOEC, 21 days: 0.0499 mg/l, Daphnia magna

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Ammonia

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Persistence and degradability The degradability of the product is not known.

3-Iodo-2-propynyl butylcarbamate

Persistence and degradability The product is readily biodegradable.

Stability (hydrolysis) pH7 - Half-life : 139 days @ 25°C

Biodegradation Water - DT₅₀ : 3.3 hours

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No data available.

Ecological information on ingredients.

Ammonia

Bio-Accumulative Potential The product is not bioaccumulating.

3-Iodo-2-propynyl butylcarbamate

Bio-Accumulative Potential log Kow: 2.81, Fish Estimated value.

Partition coefficient log Pow: 2.81

Mobility in soil

Mobility The product is water-soluble and may spread in water systems.

Ecological information on ingredients.

Ammonia

Mobility Mobile.

3-Iodo-2-propynyl butylcarbamate

Mobility Mobile.

Adsorption/desorption coefficient Soil - Koc: 61 - 309 @ 22°C

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Disposal methods Do not empty into drains. Dispose of contents/container in accordance with national regulations.

14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

UN Number

UN No. (International) Not applicable.

UN No. (DOT) Not applicable.

UN proper shipping name

Proper shipping name (International) Not applicable.

Proper shipping name (DOT) Not applicable.

Transport hazard class(es)

Transport Labels (International) No transport warning sign required.

DOT transport labels

No transport warning sign required.

Packing group

Packing group (International) Not applicable.

DOT packing group Not applicable.

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

Not applicable.

DOT reportable quantity Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed:

Phosphoric acid

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Ammonia

Final CERCLA RQ: 1000(454) pounds (Kilograms)

Acrylic acid

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

Ethyl acrylate

Final CERCLA RQ: 1000(454) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed.

SARA 313 Emission Reporting

The following ingredients are listed:

2,2-Dibromo-2-cyanoacetamide

1.0 %

3-Iodo-2-propynyl butylcarbamate

1.0 %

Ammonia

1.0 %

Acrylic acid

1.0 %

Ethyl acrylate

0.1 %

CAA Accidental Release Prevention

None of the ingredients are listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed:

Titanium dioxide

Carcinogen.

Ethyl acrylate

Carcinogen.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed:

Phosphoric acid

Acrylic acid

Ethyl acrylate

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed.

California Directors List of Hazardous Substances

The following ingredients are listed:

Phosphoric acid

Ammonia

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Proprietary

Acrylic acid

Ethyl acrylate

Massachusetts "Right To Know" List

The following ingredients are listed:

Trisodium nitrilotriacetate

Phosphoric acid

Ammonia

Titanium dioxide

Proprietary

Acrylic acid

Ethyl acrylate

Rhode Island "Right To Know" List

The following ingredients are listed:

Phosphoric acid

Titanium dioxide

Proprietary

Acrylic acid

Ethyl acrylate

Minnesota "Right To Know" List

The following ingredients are listed:

Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy- Ethane-1,2-diol, ethoxylated

Phosphoric acid

Titanium dioxide

Proprietary

Acrylic acid

Ethyl acrylate

New Jersey "Right To Know" List

The following ingredients are listed:

2,2-Dibromo-2-cyanoacetamide

3-Iodo-2-propynyl butylcarbamate

Phosphoric acid

Ammonia

Titanium dioxide

Proprietary

Acrylic acid

Ethyl acrylate

Pennsylvania "Right To Know" List

The following ingredients are listed:

Phosphoric acid

PRO-977 Ultra Prime® Pigmented Wallcovering Primer

Ammonia

Titanium dioxide

Proprietary

Acrylic acid

Ethyl acrylate

Inventories

US - TSCA

Some of the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

Abbreviations and acronyms used in the safety data sheet	ATE: Acute Toxicity Estimate. IATA: International Air Transport Association. ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. LC ₅₀ : Lethal Concentration to 50 % of a test population. LD ₅₀ : Lethal Dose to 50% of a test population (Median Lethal Dose). PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative. MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. BCF: Bioconcentration Factor. EC ₅₀ : 50% of maximal Effective Concentration. NOEC: No Observed Effect Concentration. NOAEL: No Observed Adverse Effect Level.
Training advice	Read and follow manufacturer's recommendations.
Revision comments	This is the first issue.
Revision date	8/9/2018
SDS No.	7603
Hazard statements in full	H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H335 May cause respiratory irritation. H400 Very toxic to aquatic life. H402 Harmful to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.