



PRO-999

Rx-35™, Problem Solving Sealer/Primer

Clear Sealer/Primer for Porous Surfaces

Product Number(s): 16914, 16901, 16905

Base: Proprietary specialty polymer

Product Information

General Properties: Sealer/primer that penetrates and seals porous surfaces such as torn drywall, drywall mud and spackle to enable the wall surface to be painted or wallpapered. PRO-999 seals old wallpaper paste residue (excess paste must be removed first by sanding with 80 grit sandpaper, then dust removed). PRO-999 dries clear with a slight residual tack, enhancing adhesion of paint or wallcovering.

- **Roller, brush or spray application**
- **Penetrates & seals drywall, drywall mud and spackle**
- **Seals & locks down popcorn ceilings**
- **Seals contractor's flat paint**
- **No-drip formula**
- **Low odor, no spatter**

Recommended Uses: For most porous surfaces

NOT Recommended For: Exterior surfaces, non-porous surfaces such as concrete block or cement, or direct application over oil-based primers or paints

Compatible Coatings: Most water-based products and all ROMAN® primers and adhesives

Substrates: Porous surfaces including damaged drywall or plaster, drywall mud & spackle, contractor's flat paint, popcorn ceilings, medium density fiberboard

Mildew-Resistant: All Roman products contain biocides for in-can preservation

Specification Data

Coverage: Up to approx. 350-400 square feet per gallon, depending on the porosity and texture of the surface

VOC (regulatory): ≤25 g/L

Drying Time: Minimum drying time is three hours. Optimum drying time is 12 hours. Low temperature, high humidity and poor ventilation will slow down the drying process. If applying over new drywall or unsealed surfaces, the drying time may be extended.

Roman Products, LLC – Calumet City, Illinois

For Technical Help: Call 708-891-0770 or Email: technicalhelp@romandec.com

www.romanproducts.com



Technical Data: PRO-999, Rx-35™

Updated: 06/29/22

Application Instructions

Surface Preparation: Surface must be free from grease and other residues, dry, and structurally sound. Repair drywall surfaces to required level value using appropriate spackle or mudding compound.

After completion of the required surface preparation, it is critical to test the surface with the recommended primer or adhesive to ensure compatibility. Select a small, inconspicuous area of the surface for testing and apply the primer or adhesive as specified. Inspect test area after 24 hours for any defects or inconsistencies before proceeding.

Dilution: Do not dilute.

Application Method: Use only when the room temperature is above 60 °F. Apply at recommended spread rate using a brush, roller, or spraying system. If using a spray system, back rolling is recommended. Do not overspread.

Airless Spray:	PSI Capable:	minimum 3000 PSI
	Hose:	3/8" I.D.
	Tip Size:	.015 and larger
	Gun PSI:	1500-1700

Clean-Up: Before the primer dries, remove any excess with clean water. Brushes and rollers should be cleaned immediately after use with a mild soap and clean, warm water.

Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

Limited Warranty

Roman Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

Caution

Store in a cool, dry place. DO NOT FREEZE! Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.

Roman Products, LLC – Calumet City, Illinois

For Technical Help: Call 708-891-0770 or Email: technicalhelp@romandec.com

www.romanproducts.com