



Seam Repair

Adhesive

Wallcovering Seam Repair

Base: Synthetic polymers

Product Information

General Properties: Seam repair adhesive is formulated to repair tears in wallcovering and bond vinyl to vinyl where overlapping is necessary.

- **Secures loose wallcovering seams**
- **Repairs wallcovering tears**

NOT Recommended For: Strippability. Areas where this product has been used may require repair after wallcovering has been removed.

Substrates: Will not bond to Silicone, Teflon or Tedlar type coatings

Compatible Coatings: Most paints and wallcoverings

Mildew-Resistant: All Roman products contain biocides for in-can preservation

Specification Data

Base: Synthetic polymers

VOC (actual/regulatory): 0% / 0 g/L as calculated per EPA Method 24

Storage: Avoid freezing; keep in cool, dry place.

Drying Time: Tacks up in a few minutes. May require several hours for thorough drying.

Application Instructions

Surface Preparation: Remove loose particles from behind wallpaper edge.

Dilution: Do not dilute.

Application Method: Remove cap. Apply Seam Repair adhesive in a thin, even coat. Press and smooth wallcovering into position. One application should be sufficient.

Clean-Up: Wipe off excess immediately with a damp cloth, and blot dry to ensure all residue is removed. Rinse all tools promptly with clean water.

ROMAN™

THE NO.1 CONTRACTOR BRAND

Technical Data: Seam Repair Adhesive

Updated: 1/16/18

Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Decorating Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

Limited Warranty

Roman Decorating Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

Caution

Store in a cool, dry place. DO NOT FREEZE! Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.